# From PANDJIRIS®



## **INCLUDES:**

### Mini Pro® Positioner with

- 8" chuck
- Variable Speed Range of 0.65 to 13 RPM
- 350 Pound Load Capacity
- 8.25" Swing Radius
- 2.5" Spindle Hole
- Speed and Direction Control
  - Mounted to Positioner
- 300 Amp Welding Ground On/Off Foot Switch

## Tailstock with

- Live Center (No. 2 Morse Taper)
- Filter/Regulator/Lubricator
- Locking Slide Base to Accommodate 1" to 24" Part Lengths
- Pneumatic Clamping Cylinder
- Convenient Operator Control of
  - Pneumatic Clamp
- 350 Pounds Capacity
- Optional Outboard Support Stand Available on Slide Base

### Torch Support with

- Locking Slide Base
- Vertical Rack and Pinion Adjuster
- Impingement Swivel
- Over Center Adjustment
- Lead/Lag Adjustment
- Dovetail Slides for Vertical and Cross Seam Adjustment

### Machine Base:

Aluminum Extrusion

### **Available Options:**

- Variable Speed Foot Switch
- 500 Amp Welding Ground
- Slow Speed Range
- Outboard Stand
- Weld Start/Stop Integration (Auto Rotation)

Pandjiris, Inc., 5151 Northrup Ave, St. Louis, MO 63110

Phone: 314-776-6893, Fax: 314-776-8763, www.pandjiris.com