## 20,000 LB. CAPACITY TURNTABLE **MODEL MT-200-12-VS**

The Model MT-200-12-VS Turntable is designed to support 20,000 lbs and deliver smooth variable speed table rotation. The turntable comes standard with a round table equipped with (4) radial tee slots. Standard electrical input requirement are 115 volts, 1 phase, 60 cycle. The operator controls the rotation speed and direction from a hardened plastic hand pendant on 25' of heavy rubber cable. Foot switch controls are available for direction and speed control. Wired to conform to National Electrical Code Standards.

Rotation Torque ..... 31,000 inch pounds

Rotation Drive ...... 3/4 H.P. DC Motor controlled by an SCR Variable

Speed Reversing Drive

Rotation Speed ..... 0.03 to 1.0 RPM


Control Pendant ...... Forward-Stop-Reverse, Weld/Rapid Push Buttons,

speed potentiometer on 25' of rubber covered cable.

#### MODEL MT-200-12-VS (Variable Speed)

#### **MODEL MT-200-12-CS (Constant Speed 1.0 RPM)**

Electricals 230/460 volt, 3 phase, 60 Hz. Wired to National Electrical Code



Α	Table Diameter		48"
В	Pilot Hole		6"
С	"T" Slot Quantity		(4)
	Standard ANSI "T" Nut		3/4"
D	Table Thickness		1-3/4"
Е	Table Height		24-3/8"
F	Base Dimensions	Length	42"
		Width	34"

Terms: Pandjiris, Inc. standard terms and conditions apply, f.o.b. Factory, St. Louis, Missouri, or designated ship point.

Delivery: Consult factory.

Approximate Shipping Weight: 2,500 lbs

PRICE LIST For Bulletin No. :

Effective Date

: January 2014

Page Number : I-5

Prices and specifications subject to change without notice!

### PANDJIRIS, INC

5151 Northrup • St. Louis, MO 63110 • (314) 776-6893

# MODEL MT-200-12-VS TURNTABLE Optional Accessories

For precision machined table to include "T" Slots, Pilot Hole, Table Surface, add ... Consult Factory Variable Speed Options Foot switch with compatible plug for Forward/Stop/Reverse (speed potentiometer on hand pendant) Foot switch, Fast-Slow with compatible plug Preset digital tachometer with compatible plug reads speed in RPM Dialweld®, (shows linear speed in IPM for diameter set on diameter selector. Dial diameter to be welded, dial weld speed, table RPM is automatically set to weld diameter at selected welding speed) digital meter with compatible plug reads IPM or CmPM Tach feedback for precision speed control 25' Extension Cable with compatible plugs for standard pendants and accessories For special voltages, (Other than 115 Volt, Variable Speed & Model 600 PT Copper Welding Ground Model 1200 PT Copper Welding Ground

**Terms:** Pandjiris, Inc. standard terms and conditions apply, f.o.b. Factory, St. Louis, Missouri, or designated ship point.

**Delivery:** Consult Factory

PRICE LIST

For Bulletin No. :

Effective Date : January 2014

Page Number : I-6